AMPLIDECT295 SOS PRO

Amplified Cordless Telephone with Integral Answering Machine and PENDANT included



CALLING/TALKING

- -> HAC
- -> Adjustable receiving volume : up to 30dB

eemarc™

Hear the Difference

- -Speaker phone
- -> Adjustable speaker volume
- -Phonebook up to 50 numbers
- > Redial function for last 10 outgoing calls
- > P/T dialling mode
- > R button for call waiting
- > Hotkey to phonebook
- -> Hotkey to menu
- > Flash function (100ms/300ms/600ms)
- > Large keys

HANDSET LCD DISPLAY

- > White backlight
- > Choice of 6 languages : English,
- German, French, Italian, Dutch, Spanish
- > Dimensions : 40x30mm
- -> Display : Alphanumeric / 4 lines / Characters size : 7mm
- -> Clock
- > Alarm
- > Key lock
- -> Message waiting icon
- -> Communication time indication

ANSWERING MACHINE

- 15 minutes of recording time
- > 2 announcements
- > 2 answering machine modes (simple answering machine and answering machine recorder)
- -> Visual info. on the base about number of messages
- -> 4-digit user selectable remote codes
- -> Remote control for messages on handset
- > Erase each/all messages
- → Audible time & date stamp on recorded messages
- -> 3 languages (English, German and French)

SOS-PRO 295 CHARACTERISTICS

- 5 buttons on the device : -
 - Volume +
 - Volume -
 - 2 one-touch memories
 - 1 SOS/answering incoming calls button
- SOS button :
 - Possibility to dial the 4 emergency numbers
 - Customizable emergency message or existing message 3 languages (English, French, German)
- -Adjustable ringer volume
- -> Adjustable speaker volume (5 levels)
- -Hands-free operation
- > Signal tone when the SOS-PRO 295 is out of range
- -> Visual Battery level indicator (red LED)
- -> Visual indicator when you receive a call or during a call (green LED)

SOS-PRO 295 TECHNICAL SPECIFICATION

> GAP compliant

LLAMPLIDECT295SOSPROUKV10

- 300mAh Li-Polymer battery
- Standby time : 60 hours
- Continuous in use time : 5 hours
- The SOS-PRO 295 recharge automatically when it is on the hase
- -Indoor range : 30 meters
- Open field range : 200 meters
- -Receiver weight : 61g

Included accessories: **SOS-PRO 295**

2 one-touch memories

SOS-PRO 295

AmpliDect295 AD

(-)

13

PhotoDect295

eemarc™

www.geemarc.com

Telecom SA

1 SOS/answering incoming calls button

RINGER

ge

T

6

2 Ģ

2400 300

5 - 6-

8 TAN 9 m

0 #×

1 0 R

SOS-PRO

- > Extra loud ringtones: up to 75dB on the handset and 80dB on the base
- → 5 polyphonic ringtones and 5 normal

Pe

sos

- -> Adjustable ring volume (Mute + 5 positions)
- -Customizable ringtones for phonebook contacts
- -> Ringer indicator

MULTI HANDSET

- -> Handset locator
- -> 3-way conference with privacy protection
- -> Up to 4 bases and up to 5 handsets
- -> Call transfer of external calls (when using several handsets)
- -> Intercom between handset

TECHNICAL SPECIFICATIONS

- 1 battery ni-Mh 2.4V 500mA (included)
- > Memory storage

>

CER

M2

- -> Power supply by AC adapter (supplied)
- > Dial/Decimal voice frequency
- -Standby time : 2 days
- -> Continuous talk time : 8 hours
- > GAP compliant •
 - Range :
 - Indoor : up to 50m 0
 - 0 Open field : up to 300m
- -> Dimensions :
 - Handset :172x55x25 mm 0
 - Base : 136x91x105 mm 0

CALLER ID *

Name presentation in hook mode (type 1)

(SOS functions are not accessible

(SOS functions are not accessible

from the additional handset)

from the additional handset)

- and conversation mode (type 2)
- 20 incoming numbers 0
- 10 outgoing numbers 0 -Caller ID also for Call waiting
- -> Possibility to transfer a call received
- to the directory
- -Indicator call waiting
- > Indicator new call

OPTIONAL EXTRA

SOS-PRO 295

PhotoDect295

AmpliDect295 AD

->

>

->

*To use the CID facility it will be necessary to subscribe to your network provider's CID service. Items pictured and details are subject to change at the manufacturer's discretion.