

FEMTO S

1.186



Allowed user weight

130 kg



Suitable for passenger transport






*Reduziertes Rahmendesign



*Lenkradeinstellung



*Einstellbarer Rückenwinkel



*Multifunktionale Beinstütze

FUSE Together

EFFICIENCY

- Permanent provision with adjustment possibilities to functional changes reduces follow-up costs
- Extensive serial equipment minimises necessity for expensive customised parts
- Little wear and proneness to repair through integral design of the frame and the quality of the attachment components

THERAPEUTIC BENEFIT

- Perfect easy running and little own weight support the independence of the user
- Adaptable to functional changes and individual needs of the user through adjustment of the back, seat and chassis
- Extensive equipment assortment for long-term users
- Compact sitting, driving and transport through the optimal frame design
- Adjustable seat and back strap, individually adjustable back height
- Optimum mobility traits: lighter, sportier, easier to tilt and turn

FIELD OF USE

- For permanent and long term provision
- Very good suitability for many disease patterns, even for severely encumbered
- *Abnehmbare Armlehnen, höhen- und tiefenverstellbar

ORDER

COST ESTIMATE

CUSTOM DESIGN

Please send the order form by e-mail to:

info@meyragroup.com

Customer service: +49 571 93292 555

Billing address / Customer ref. no.:

Delivery address:

Tax-ID

Consignment / Comments:

Order quantity:

MEYRA



Basic equipment

- Plastic castor
- Aluminum rear wheel
- Camber 0°
- High-pressure tires
- Stainless steel push rims
- Pressure Brake

- Back angle
- Black textile backrest cover
- Push handle short
- Plastic side guard
- Plastic base plates
- Frame colours



Allowed user weight

130 kg



Suitable for passenger transport



Hints

Our Terms and Conditions as stated at www.meyra.de/AGB shall apply

You can find information on the measurement process at www.meyra.de/messverfahren

Valid from 01.01.2025 – 31.12.2025.

Errors, misprints and changes reserved.

Use our K.I.S.S.S. for orders and configurations at www.kisss-by-meyra.de

You avoid queries and incorrect orders thanks to the buildability check

**Technical specifications**

Seat widths in mm	320/340/360/380/400/420/440/460/480/500/520
Width ready to drive in mm from	*Sitzbreite +170
Width folded in mm from	280 with 0° wheel camber or 330 with 3° wheel camber
Seat depth in mm	340/360/380/400/420/440/460/480/500
Seat height front/rear in mm	*425 bis 560 / 390 bis 530
Overall height in mm	Rear seat height + back support height
Back support height in mm	*variabel von 250 bis 500 verstellbar in 15mm Schritte
Arm support height in mm	ca. 170 - 245
Length with footrest in mm	880 - 1030 (depending on frame length, wheel size and axis position)
User weight	130 kg
Empty weight from	9,5 kg
*Zul. Gesamtgewicht in kg	145 kg
Transport weight	7,4 kg
Rear wheel	600 mm (24") / 635 mm (25") / 660 mm (26")
Brake test according to STANDARD	7°

☐ Please select by ticking the relevant boxes

S

 Special construction/individual solution o.r. - on request

Standard version: If no other selection is made, the standard version will be delivered.

01 Frame shape / seat width / seat depth

	(C-394)	(C-366)	(C-368)	(C-615)	(C-784)	(C-618)	(C-619)	(C-787)	(C-792)
Seat width/Seat depth	SD 340 mm	SD 360 mm	SD 380 mm	SD 400 mm	SD 420 mm	SD 440 mm	SD 460 mm	SD 480 mm	SD 500 mm
SW 320 mm (C-32)									
SW 340 mm (C-34)									
SW 360 mm (C-36)									
SW 380 mm (C-38)									
SW 400 mm (C-40)									
SW 420 mm (C-342)									
SW 440 mm (C-344)									
SW 460 mm (C-46)									
SW 480 mm (C-48)									
SW 500 mm (C-350)									
SW 520 mm (C-952)									

including utensil pocket under the seat belt

03 Front seat height (FSH) in combination with castor wheel (without seat cushion)

The max permissible seat height difference between front and rear seat height is 100 mm!

		Front seat height in mm (FSH)												
Code	Castor	440	450	460	470	480	490	500	510	520	530	540	550	560
151/908	Ø 100 Solid rubber black													
151/909	Ø 100 Solid rubber grey													
325/908	Ø 125 Solid rubber black													
325/909	Ø 125 Solid rubber grey													
327/908	Ø 142 Soft-solid rubber black													
327/909	Ø 142 Soft-solid rubber grey													

☐ Please select by ticking the relevant boxes

S

 Special construction/individual solution o.r. - on request

☐ Standard version: If no other selection is made, the standard version will be delivered.

Front seat height (FSH) in combination with castor wheel (without seat cushion)

		Front seat height in mm (FSH)											
Code	Castor	440	450	460	470	480	490	500	510	520	530	540	550
2480	Ø 100 x 23 Lightwheel black												
2481	Ø 100 x 32 Castor aluminum silver												
2482	Ø 125 x 32 Castor aluminum silver												

Tires: CODE 2480 solid rubber, transparent/colored - CODE 2481/2482 solid rubber black

Seat height front in combination with carbon castor (without seat cushion)

		Front seat height in mm (FSH)											
Code	Castor	440	450	460	470	480	490	500	510	520	530	540	550
2495	Ø 100 x 30 mm, Black												
2496	Ø 125 x 30 mm, Black												

Tyres: solid rubber, black

☐ Please select by ticking the relevant boxes

S

 Special construction/individual solution o.r. - on request

☐ Standard version: If no other selection is made, the standard version will be delivered.

Seat height front in combination with aluminium castor (without seat cushion)

Code	Castor	Front seat height in mm (FSH)											
		440	450	460	470	480	490	500	510	520	530	540	550
2483	Ø 100 x 37 mm, Silver												
2484	Ø 100 x 37 mm, Black												
2485	Ø 100 x 37 mm, White												
2486	Ø 100 x 37 mm, Red												
2487	Ø 100 x 37 mm, Blue												
2488	Ø 100 x 37 mm, Orange												
2489	Ø 125 x 37 mm, Silver												
2490	Ø 125 x 37 mm, Black												
2491	Ø 125 x 37 mm, White												
2492	Ø 125 x 37 mm, Red												
2493	Ø 125 x 37 mm, Blue												
2494	Ø 125 x 37 mm, Orange												

 Tyres: solid rubber, black

☐ Please select by ticking the relevant boxes☒ Special construction/individual solution o.r. - on request☐ Standard version: If no other selection is made, the standard version will be delivered.**04 Rear wheels i.c. with seat height (tires CAT 07 and hand rims CAT 06)**

The maximum permissible seat height difference between the front and rear seat height is 90 mm

*HSH (mm) 26 Zoll 390 400 410 420 430 440 450 460 470 480 490 500 510 520 530

A
B
C

CODE	RSH	DESCRIPTION	Ø
651	A	Standard wheel, incl. quick release axle (pair)	24"
2651	A	Standard wheel black, incl. quick release axle (pair)	24"
706	A	Drum braked wheel with radial spokes and drum brake for accompanying person  Only in conjunction with push handles CODE 412 or 502 Wheel overlap CODE 98 is recommended.	24"
848	A	SILVERDESIGN with radial spokes and high flange rim incl. quick-release axle (pair)	24"
695	A	Active-wheel with radial spokes, high flange rim, hollow rim (Jumbo rim) in black  Not in conjunction with PU tires CODE 902 Carbolife handrims CODE 849, 850, 853 Recommended from 100 kg user weight or with dynamic driving style	24"
695	B	Active-wheel with radial spokes, high flange rim, hollow rim (Jumbo rim) in black  Not in conjunction with PU tires CODE 902 Carbolife handrims CODE 849, 850, 853 Recommended from 100 kg user weight or with dynamic driving style	25"
695	C	Active-wheel with radial spokes, high flange rim, hollow rim (Jumbo rim) in black  Not in conjunction with PU tires CODE 902 Carbolife handrims CODE 849, 850, 853 Recommended from 100 kg user weight or with dynamic driving style	26"
2469	A	Spinergy CLX, carbon rear wheel, spokes and hub black	24"
2470	A	Spinergy LX, aluminum rear wheel, spokes, rim and hub black	24"
2471	A	Spinergy LX, aluminum rear wheel, rim and hub black, spokes white	24"
2472	A	Spinergy LX, aluminum rear wheel, rim and hub black, spokes orange	24"

☐ Please select by ticking the relevant boxes

S

 Special construction/individual solution o.r. - on request

Standard version: If no other selection is made, the standard version will be delivered.

Rear wheel i.c. with seat height (incl. tyre and handrim)

The max permissible seat height difference between front and rear seat height is 100 mm!

*HSH (mm) 25 Zoll 390 400 410 420 430 440 450 460 470 480 490 500 510 520

A

B

CODE	RSH	DESCRIPTION	Ø
752	A	Lightwheel incl. RightRun Light tyres and aluminum handrim black	24"
2466	A	Cross-Rad incl. coarse studded tyres and stainless steel handrims (pair)	24x1.75"
2461	A	Day-Lite aluminium drive wheel, black rim, hub and spokes, black aluminium handrim and black MBL Gazelle tyres. ⚠ max. user weight 100kg	24x1"
2468	B	Day-Lite aluminum rear wheel, black rim, hub and spokes, black aluminum handrim and black MBL Speedlite tyres. ⚠ max. user weight 100kg	25x1"
2473	A	Blacklight aluminum rear wheel, incl. Schwalbe Marathon Plus tyres and aluminum push rims, rim, hub and spokes black	24x1"

⚠ Complete wheels - please do not select handrims and tyres!

05 Horizontal rear wheel position (center of gravity)

ACTIVE (Pos.-mm)		MEDIUM (Pos.-mm)			PASSIV (Pos.-mm)		
1 - 115	2 - 95	3 - 75	4 - 55	5 - 35	6 - 15	7 - (-5)	8 - (-25)
Position							

⚠ Measuring method: Rear edge of back tube to axle center in mm

☐ Please select by ticking the relevant boxes☒ Special construction/individual solution o.r. - on request☐ Standard version: If no other selection is made, the standard version will be delivered.

Rear wheel options

CODE	DESCRIPTION
697	Release for tetra plegics, makes it easier to take off the drive wheel  Only in conjunction with drive wheel CODE 848 or CODE 695
478	0° wheel camber
447	3° wheel camber (track adjustable, wheel camber can be altered subsequent-ly) in combination with drum brake CODE 706 restricted seat height variation

06 Handrims and handrim options

CODE	DESCRIPTION			
445	Titanium, with 6 brackets  Only in conjunction with Active wheel CODE 695 Spinergy wheel CODE 2469, 2470, 2471, 2472	24"	25"	26"
493	Stainless steel, polished	24"	25"	26"
494	Aluminum silver anodised  Not in conjunction with active wheel CODE 695	24"		
168	Optigripp-special handrim for tetraplegics	24"		
849	Curve L, aluminum black anodised, ergonomic handrim profile, H 31 mm	24"		
850	Curve L Tetra Grip, anti-slip coated, aluminum, suitable for quadriplegics, ergonomic handrim profile, H 31 mm	24"		
853	Gekko, aluminum black anodized with replaceable rubber lip, ergonomic handrim profile, H 31mm	24"		
166	Silicon hand rim cover, smooth, black  Not in conjunction with aluminum push rims CODE 494	24"		
692	Handrim distance narrow			
693	Handrim distance far			

☐ Please select by ticking the relevant boxes☒ Special construction/individual solution o.r. - on request☐ Standard version: If no other selection is made, the standard version will be delivered.**07 Tyres**

CODE	DESCRIPTION	Ø
496	High pressure tyre 8 bar	24x1"
486	Pneumatic tires with grooved tread, 4 bar	24x1 3/8"
902	PU-tyres, puncture safe  Not in conjunction with active wheel CODE 695	24x1"
897	Marathon-Plus-Evolution tyres, puncture protected	24x1"
363	Schwalbe ONE tyre, no profile, puncture resistant	24x1"
395	Maxxis VN Master Alpha Protect tyre black, puncture resistant, 10 bar	24x1"
474	PU-tyres, puncture safe black  Not in conjunction with active wheel CODE 695	24x1"

 Tyres consist of a rubber compound which may leave permanent marks or be hard to remove from some surfaces (e.g. plastic, wooden or parquet flooring, rugs and carpets).
We cannot accept liability for any abrasion damage to flooring.

08 Brakes

CODE	DESCRIPTION
305	Pressure brake for user
60/650	One-hand pressure brake left (incl. Brake lever long, hinged)
74/650	One-hand pressure brake right (including brake lever long, hinged)
2595	Light pressure brake made of aluminum, swing away
681	Brake lever extension, foldable, firmly mounted  *Nur in Verbindung mit Druckbremse CODE 305
986	Attachable brake lever extension  *Nur in Verbindung mit Druckbremse CODE 305

☐ Please select by ticking the relevant boxes☒ Special construction/individual solution o.r. - on request☐ Standard version: If no other selection is made, the standard version will be delivered.**09 Backrest height (BH)**

Backrest height in mm

(C-620) (C-626) (C-631) (C-632) (C-633) (C-637)

DESCRIPTION	250	300	350	400	450	500
-------------	-----	-----	-----	-----	-----	-----

*Rückengurt, über Klettbänder anpassbar nachträglich einstellbar +60 mm (15mm Schritte)						
---	--	--	--	--	--	--

Back angle

Pos. A

Pos. B

Pos. C

Pos. D

Pos. E

80°

85°

90°

95°

100°

 The smaller the angle, the more the back is inclined towards the seat**Backrest variants**

CODE DESCRIPTION

2002 Back cover 20 mm wider

2003 Back cover 40 mm wider

593 Without back cover

 recommended when using RIDE back systems**Back strap colours (seat strap always in black)**

CODE DESCRIPTION

235 Textil black

292 Mash, breathable , black

☐ Please select by ticking the relevant boxes☒ Special construction/individual solution o.r. - on request☐ Standard version: If no other selection is made, the standard version will be delivered.**10 Backrest**

CODE	DESCRIPTION
411	Backrest without push handle
410	Back with push handle, long
413	Back with push handle, short
141	Push handles, swivel-away
502	Backrest with push handle mounted to the frame tube, continuously height adjustable to 150 mm

Backrest options

CODE	DESCRIPTION
2032	ErgoSeat Pro laterals, small, pair  Recommended at back height 300 - 400 mm
818	Backrest can be folded forward onto the seat

11 Ride System Back

Please specify the CODE from the RIDE order sheet:

☐ Please select by ticking the relevant boxes☒ Special construction/individual solution o.r. - on request☐ Standard version: If no other selection is made, the standard version will be delivered.**12 Seat cushions**

CODE	DESCRIPTION
560	Seat cushion 30 mm
561	Seat cushion 60 mm
7199	Netti Contour Breathable 3D cover
562	Velcro strip on seat belt

13 Ride System Seat

Please specify the CODE from the RIDE order sheet:

14 Arm supports and arm pads

1 = fixed screwed 2 = swivel up 3 = detachable 4 = lockable 5 = height-adjustable armrest 6 = with wheel cover

CODE	DESCRIPTION	FUNCTIONS
101	*Seitenteil aus Kunststoff  *Radspritzschutz 41mm	3,6
100	Side guard made of aluminium in black with cold protection insert  *Radspritzschutz 35mm	1,6
783	Carbon fiber side guard  *Radspritzschutz 35mm	1,6
304	Carbon fiber side guard  Without mudguard	
81	Side guard, short upholstered armrest, height-adjustable with one-hand operation  *bei hinterer Sitzhöhe kleiner als 460mm, eingeschränkte Höhenverstellung der Armlehne nach unten	2,3,4,5
84	Side guard, large upholstered armrest, height-adjustable with one-hand operation  *bei hinterer Sitzhöhe kleiner als 460mm, eingeschränkte Höhenverstellung der Armlehne nach unten	2,3,4,5

Side panel option

CODE	DESCRIPTION
24	Swing-away side panel bracket  *nicht in Verbindung mit Seitenteil CODE 81/84

☐ Please select by ticking the relevant boxes S Special construction/individual solution o.r. - on request
☐ Standard version: If no other selection is made, the standard version will be delivered.

15 Leg supports

CODE	DESCRIPTION	
93	*abnehm-, wegschwenkbar 70°	Pair
759	Removable, swing away	Left
760	Removable, swing away	Right
293	*kompakt 80°	Pair
94	without leg rests	

Footrests

LLL (mm) 370 380 390 400 410 420 430 440 450 460 470 480 490 500 510 520																
A																
CODE	LSL	DESCRIPTION	depth													
805	A	Split plastic footrests, fold-up and height-adjustable ⚠️ *ab SB 340mm														
312	A	Footrest made of sturdy aluminum profile in frame color, foldable, height and angle adjustable														
808	A	Footrests divided, up-folding, depth adjustable, height and angle adjustable	150 mm													

Footrests options

CODE	DESCRIPTION
359	Calf belt

☐ Please select by ticking the relevant boxes

S

 Special construction/individual solution o.r. - on request

☐ Standard version: If no other selection is made, the standard version will be delivered.

16 Frame colours

CODE	DESCRIPTION
130	Titanium grey
206	Matt black
224	Blue-Metallic
227	Red Metallic
4044	Red Metallic Matt
4049	Olive green Matt
4050	Sky Blue
4051	Chalk
4919	Silverline
4922	Metallic green

☐ Please select by ticking the relevant boxes☒ S Special construction/individual solution o.r. - on request☐ Standard version: If no other selection is made, the standard version will be delivered.**17 Options****hand and spoke protection**

CODE	DESCRIPTION
489	Transparent  *nicht in Verbindung mit Spinergy Rad CODE 2469, 2470, 2471, 2472

Support castors

CODE	DESCRIPTION
728	Anti-Tip, 1 pair, swivelling (recommended)  Not in conjunction with Support tube CODE 309
729	1 anti-tip, swivelling, mounted left  *nicht in Verbindung mit Auftrittrohr CODE 309/4930 Rangierrollen CODE 746
730	1 anti-tip, swivelling, mounted right  *nicht in Verbindung mit Auftrittrohr CODE 309/4931 Rangierrollen CODE 746

Other accessories

CODE	DESCRIPTION
309	Step tubes (1 pair)
4930	1 step tube, mounted on the left  not in combination with anti-tip-wheels, CODE 691/712 and anti-tip-wheels, CODE 746
4931	1 step tube, mounted on the right  not in combination with anti-tip-wheels, CODE 691/713 and anti-tip-wheels, CODE 746
833	Safety belt
819	Reflectors  not in v.v.m. CODE 752, 2473, 2461 and 2468
970	Crutch holder  only i.V. with tread pipe CODE 309/4930/4931 or CODE 691/712/713

☐ Please select by ticking the relevant boxes☒ Special construction/individual solution o.r. - on request☐ Standard version: If no other selection is made, the standard version will be delivered.

Therapy tables

CODE	DESCRIPTION
929	Therapy table plastic, transparent, adjustable from 380 - 480 mm seat width  Only in conjunction with Sideguard CODE 84 Seat width 400 - 480mm
930	Therapeutic table for manual wheelchairs made of plastic, transparent, for sliding on, for defined seat width  only in conjunction with side panel CODE 84

 With 24" wheels and a rear seat height of less than 470 mm, there is a resulting limitation in terms of armrest height with use of the therapy table Code 929/930

Xtrends options

CODE	DESCRIPTION
962	X-TREME Backpack
2080	Wheel pouch „BLACK WHEEL CASE“ fitting for max. 2 x 24" wheels resp. each 1 x 25" or 26" wheel
2081	Wheel pouch „MEYRA ACTIVE“, fitting for max. 3 x 28" wheels
2082	3M Spoke reflectors