

BEN4 Plus

Semi adjustable budget rehab-stroller





DESIGN OPTIONS



Robust and time-proven durable undercarriage with ergonomically shaped handle and 200/300 mm wheels along with 4 seat-sizes (MINI, Standard, MAXI, SuperMaxi 42) are the base for the standard line of rehab-strollers. BEN 4 Plus – line is equipped with fully foldable undercarriage, produced of the light weight thin-walled tubes with powder coated surface finishing. Undercarriage is reinforced and optimized for heavy duty usage. Non size adjustable seat with option of 3 angle positions and height adjustable footrest is covered by fully detachable soft padded textile upholstery in fashionable design. The stroller can be optionally equipped with wider variety of special fixing devices and accessories. Easy handling is ensured by the stroller's fully and very compact foldable frame as well by the stroller's big wheels. The correct usage of the product should be consulted with a seating specialist.

The product corresponds to the newest EC standards as well as hygienic, technical and safety requirements.

Standard equipment:

- non size-adjustable seat with fully detachable soft padded textile upholstery
- fully reclining backrest
- seat with tilt-in space function (3 positions)
- height variations for attaching of the fixation devices and accessories
- angle and height adjustable footrest
- 200/300 mm wheels
- detachable grab bar with cover
- frame color and fabric patterns according to the current offer
- height adjustable ergonomic handlebar

Optional equipment:

- · canopy, rain cover
- headrest, 4-point immo.belt, abductor wedge and other equipment according to the actual list
- · work board
- basket

Or	der	CO	des:
\mathbf{v}	uci	CO	ucs.

BEN 4 Plus MINI:
BEN 4 Plus STD:
BEN 4 Plus STD:
BEN 4 Plus MAXI:
BEN 4 Plus MAXI:
BEN 4 Plus SuperMaxi 42:
B4PWKPXYY
B4PWKPS2Y

MINI	STD	MAXI	SuperMaxi42
530	630	710	710
250	280	360	360
300	340	370	400
190-330	190-330	220-380	220-380
0° - 165°	0° - 165°	0° - 165°	0° - 165°
17°/ 20°/ 23°	17°/ 20°/ 23°	17°/ 20°/ 23°	17°/ 20°/ 23°
1020	1020	1040	1040
580	580	620	680
1045	1045	1080	1080
foot oper.	foot oper.	foot oper.	foot oper.
15,0 kg	17,0 kg	18,0 kg	20,0 kg
35,0 kg	35,0 kg	50,0 kg	75,0 kg
940	940	940	940
580	580	620	680
430	430	430	430
	530 250 300 190-330 0° - 165° 17°/20°/23° 1020 580 1045 foot oper. 15,0 kg 35,0 kg 940 580	530 630 250 280 300 340 190-330 190-330 0°-165° 0°-165° 17°/20°/23° 17°/20°/23° 1020 1020 580 580 1045 1045 foot oper. foot oper. 15,0 kg 17,0 kg 35,0 kg 35,0 kg 940 940 580 580	530 630 710 250 280 360 300 340 370 190-330 190-330 220-380 0°-165° 0°-165° 0°-165° 17°/20°/23° 17°/20°/23° 17°/20°/23° 1020 1020 1040 580 580 620 1045 1045 1080 foot oper. foot oper. foot oper. 15,0 kg 17,0 kg 18,0 kg 35,0 kg 50,0 kg 940 940 940 940 580 580 620



